

|   |   |
|---|---|
| <b>Description:</b>                       | Bollard Bravo 750mm                     |
| <b>Item number:</b>                       | DFBO50-20                               |
| <b>GTIN:</b>                              | 4250912311329                           |
| <b>Customs tariff number:</b>             | 39269097                                |
| <b>Material:</b>                          | Polyethylene                            |
| <b>Width (mm):</b>                        | 225                                     |
| <b>Height (mm):</b>                       | 750                                     |
| <b>Depth/Length (mm):</b>                 | 225                                     |
| <b>Diameter (mm):</b>                     | 200                                     |
| <b>Net weight (kg):</b>                   | 16,12                                   |
| <b>Gross weight (kg):</b>                 | 17,091                                  |
| <b>Width without foot plate (mm):</b>     | 200                                     |
| <b>Depth without foot plate (mm):</b>     | 200                                     |
| <b>Colour:</b>                            | Yellow - black                          |
| <b>Foot plate width (mm):</b>             | 225                                     |
| <b>Foot plate depth (mm):</b>             | 225                                     |
| <b>Foot plate height (mm):</b>            | 10                                      |
| <b>Foot plate colour:</b>                 | Black                                   |
| <b>Area of application:</b>               | Indoor and outdoor use                  |
| <b>Mounting:</b>                          | Bolting                                 |
| <b>Delivery is:</b>                       | Pre-assembled                           |
| <b>Number of mounting holes:</b>          | 4                                       |
| <b>Fixing included:</b>                   | Concrete screw anchors M12 x 80 mm      |
| <b>Tested to withstand force (Joule):</b> | IMPACT ZONE 4: 90° 4.000 J              |
| <b>Vehicle:</b>                           | LPG forklift                            |
| <b>Vehicle weight equivalent (kg):</b>    | 4.320 kg                                |
| <b>Vehicle equivalent speed (km/h):</b>   | 4,9 km/h                                |
| <b>Approval / Certification:</b>          | TÜV-GS certified PAS 13: 2017 Kap 7/7.8 |
| <b>Inclination angle:</b>                 | 15°                                     |
| <b>Chemical Resistance:</b>               | High-ISO/TR 10358                       |
| <b>Temperature Range:</b>                 | -40° bis +50°                           |
| <b>Recyclability:</b>                     | 100%                                    |
| <b>Warranty:</b>                          | 5 years                                 |
| <b>Brand:</b>                             | D-flexx                                 |

