Polyurethane foam Yellow - black Light and weather-resistant adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Flexible Temperature-resistant -40°C to 100°C			
Yellow - black Light and weather-resistant adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Flexible Temperature-resistant -40°C to 100°C			
Light and weather-resistant adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Flexible Temperature-resistant -40°C to 100°C			
adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Flexible Temperature-resistant -40°C to 100°C			
Temperature-resistant -40°C to 100°C			
Temperature-resistant -40°C to			
Length +/- 5%			
Mounting / Fixing			
Indoor and outdoor use			
Self-adhesive			
Machines Mobile inventory Vehicles Walls Passageways			
Generel information			
39259010			
Firetesting DIN EN 13501-1 / Class E			
1 year			




- Resistant to oils, greases and many solvents.
- Simple and cost-effective installation.
- Protective film for warning marks longer lifetime.



info@dancop.com

We reserve the right to amend specifications without notice or obligation



Item number	GTIN	Depth/Length (mm)	Net weight (kg)
WPP004001	4250912301801	1000	0,793