
Corner protection wall Kit A yellow-black

| Product characteristics | | | |
|--------------------------|--|--|--|
| Material | Polyurethane foam INOX | | |
| Colour | Yellow - black | | |
| Features | Light and weather-resistant adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 | | |
| Material properties | Flexible Temperature-resistant -40°C to 100°C Moisture-resistant Shore hardness (Shore A), approx. 45 | | |
| Dimensions | | | |
| Tolerance deviation | Length +/- 5% | | |
| Mounting / Fixing | | | |
| Area of application | Indoor and outdoor use | | |
| Mounting | Screw together | | |
| Mounting location | Machines Mobile inventory Vehicles Walls Passageways | | |
| Generel information | · | | |
| Customs tariff number | 39259010 | | |
| Approval / Certification | Firetesting DIN EN 13501-1 / Class E | | |
| Warranty | 1 year | | |
| Item number GTIN | Denth/Length (mm) Net | | |

| Item number | GTIN | Depth/Length (mm) | Net weight (kg) |
|-------------|---------------|-------------------|-----------------|
| WPP036001 | 4250912307360 | 1000 | 0,78 |



- Resistant to oils, greases and many solvents.
- Simple and cost-effective installation.
- Protective film for warning marks longer lifetime.



www.dancop.com info@dancop.com

Ne reserve the right to amend specifications without notice or obligation.