
Corner protection wall Kit E yellow-black

Material Polyurethane foam INOX Colour Yellow - black Features Light and weather-resistant adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Material properties Flexible Temperature-resistant -40 °C to 100 °C Moisture-resistant Shore hardness (Shore A), approx. 40 Dimensions Tolerance deviation Length +/- 5% Mounting / Fixing Area of application Indoor and outdoor use Mounting Screw together Mounting Iocation Machines Mobile inventory Vehicles Walls Passageways Generel information Customs tariff number 39259010	Product characteristics		
INOX Colour Yellow - black Features Light and weather-resistant adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Material properties Flexible Temperature-resistant -40°C to 100°C Moisture-resistant Shore hardness (Shore A), approx. 40 Dimensions Tolerance deviation Length +/- 5% Mounting / Fixing Area of application Mounting Screw together Mounting Iocation Machines Mobile inventory Vehicles Walls Passageways General information Customs tariff number 39259010			
Features Light and weather-resistant adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Material properties Flexible Temperature-resistant -40°C to 100°C Moisture-resistant Shore hardness (Shore A), approx. 40 Dimensions Tolerance deviation Length +/- 5% Mounting / Fixing Area of application Mounting Screw together Mounting location Machines Mobile inventory Vehicles Walls Passageways General information Customs tariff number 39259010	Material	1 7	
adhesive Adhesive strength 21N/25mm Hatched according to ASR A1.3 Material properties Flexible Temperature-resistant -40°C to 100°C Moisture-resistant Shore hardness (Shore A), approx. 40 Dimensions Tolerance deviation Length +/- 5% Mounting / Fixing Area of application Indoor and outdoor use Mounting Screw together Mounting location Machines Mobile inventory Vehicles Walls Passageways General information Customs tariff number 39259010	Colour	Yellow - black	
Temperature-resistant -40 °C to 100 °C Moisture-resistant Shore hardness (Shore A), approx. 40 Dimensions Tolerance deviation Length +/- 5% Mounting / Fixing Area of application Indoor and outdoor use Mounting Screw together Mounting Iocation Machines Mobile inventory Vehicles Walls Passageways General information Customs tariff number 39259010	Features	adhesive Adhesive strength 21N/25mm	
Tolerance deviation Length +/- 5% Mounting / Fixing Area of application Mounting Screw together Mounting location Machines Mobile inventory Vehicles Walls Passageways Generel information Customs tariff number Screw together Machines Mobile inventory Vehicles Walls Passageways	Material properties	Temperature-resistant -40°C to 100°C Moisture-resistant Shore hardness (Shore A), approx.	
Mounting / Fixing Area of application Indoor and outdoor use Mounting Screw together Mounting Iocation Machines Mobile inventory Vehicles Walls Passageways Generel information Customs tariff number 39259010	Dimensions		
Area of application Indoor and outdoor use Mounting Screw together Mounting location Machines Mobile inventory Vehicles Walls Passageways Generel information Customs tariff number 39259010	Tolerance deviation	Length +/- 5%	
Mounting Screw together Mounting location Machines Mobile inventory Vehicles Walls Passageways Generel information Customs tariff number 39259010	Mounting / Fixing		
Mounting location Machines Mobile inventory Vehicles Walls Passageways Generel information Customs tariff number 39259010	Area of application	Indoor and outdoor use	
Mobile inventory Vehicles Walls Passageways Generel information Customs tariff number 39259010	Mounting	Screw together	
Customs tariff number 39259010	Mounting location	Mobile inventory Vehicles Walls	
	Generel information		
A 1/0 (C) E	Customs tariff number	39259010	
Approval / Certification Firetesting DIN EN 13501-1 / Class E	Approval / Certification	Firetesting DIN EN 13501-1 / Class	
Warranty 1 year		<u> </u>	



- Resistant to oils, greases and many solvents
- Simple and cost-effective installation.
- Protective film for warning marks longer lifetime.



info@dancop.com

We reserve the right to amend specifications without notice or obligation

Item number	GTIN	Depth/Length (mm)	Net weight (kg)
WPP037001	4250912307377	1000	0,57